

Recommended Practice for Installation, Maintenance and Repair of Surface Safety Valves and Underwater Safety Valves Offshore

API RECOMMENDED PRACTICE 14H
FIFTH EDITION, AUGUST 2007



Recommended Practice for Installation, Maintenance and Repair of Surface Safety Valves and Underwater Safety Valves Offshore

Upstream Segment

API RECOMMENDED PRACTICE 14H
FIFTH EDITION, AUGUST 2007



SPECIAL NOTES

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed. Where applicable, authorities having jurisdiction should be consulted.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

Users of this Recommended Practice (RP) should not rely exclusively on the information contained in this document. Sound business, scientific, engineering, and safety judgement should be used in employing the information contained herein.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 1220 L Street, N.W., Washington, D.C. 20005.

Copyright © 2007 American Petroleum Institute

FOREWORD

This Recommended Practice (RP) is under the jurisdiction of the API Subcommittee on Valves and Wellhead Equipment.

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API Standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 1220 L Street, N.W., Washington, D.C. 20005. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API Standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually and updated quarterly by API, 1220 L Street, N.W., Washington, D.C. 20005.

Suggested revisions are invited and should be submitted to the Standards and Publications Department, API, 1220 L Street, NW, Washington, D.C. 20005, standards@api.org.

Copyright American Petroleum Institute
Provided by IHS under license with API
No reproduction or networking permitted without license from IHS

CONTENTS

	Page
1 SCOPE.....	1
2 DEFINITIONS.....	1
3 RECEIVING INSPECTION.....	2
4 INSTALLATION AND MAINTENANCE.....	2
5 REPAIR.....	3
5.1 Onsite Repair of SSVs/USVs	3
5.2 Offsite Repair/Remanufacture of SSVs/USVs	3
6 TESTING PROCEDURES.....	3
6.1 Periodic SSV Operating and Pressure Holding Test.....	3
6.2 Periodic USV Operating and Pressure Holding Test	3
6.3 Testing After Onsite Repairs	4
7 FAILURE REPORTING.....	4
8 DOCUMENTATION REQUIREMENTS	5
9 MISCELLANEOUS	5
APPENDIX A SAMPLE PRESSURE BUILDUP CALCULATION.....	11
APPENDIX B SI UNITS	15
Tables	
B-1 SI Units	15

Recommended Practice for Installation, Maintenance and Repair of Surface Safety Valves and Underwater Safety Valves Offshore

1 Scope

1.1 One of the means of assuring positive wellstream shutoff is the use of the wellhead surface safety valve (SSV) or underwater safety valve (USV). It is imperative that the SSV/USV be mechanically reliable. It should therefore be operated, tested and maintained in a manner to assure continuously reliable performance.

1.2 The purpose of this Recommended Practice (RP) is to provide guidance for inspecting, installing, operating, maintaining, and onsite repairing SSVs/USVs manufactured according to API Spec 6A (17th Edition or later), Clause 10.20 or API Spec 14D (withdrawn). Included are procedures for testing SSVs/USVs.

1.3 This RP covers guidelines for inspecting, installing, maintaining, onsite repairing, and operating SSVs/USVs. Nothing in this RP is to be construed as a fixed rule without regard to sound engineering judgment nor is it intended to override applicable federal, state or local laws.

2 Definitions

The following definitions are related specifically to surface safety valves and underwater safety valves and are presented to define the terminology used in this standard.

2.1 failure: Improper performance of a device or equipment item that prevents completion of its design function.

2.2 heat sensitive lock open device: A device installed on a SSV actuator to maintain the SSV valve in a full open position until exposed to sufficient heat to cause the device to release and allow the SSV valve to close.

2.3 manufacturer: The principal agent in the design, fabrication, and furnishing of a SSV/USV actuator and/or SSV/USV valve. The SSV/USV valve and SSV/USV actuator define functional entities and do not necessarily represent the units as supplied.

2.4 operating manual: The publication issued by the manufacturer containing detailed data and instructions related to the design, installation, operation, and maintenance of SSV/USV equipment.

2.5 operator: The user of a SSV/USV who chooses to comply with this standard.

2.6 qualified part: A part manufactured under an authorized quality assurance program and, in the case of replacement, produced to meet or exceed the performance of the original part.

2.7 qualified person: An individual with characteristics or abilities gained through training or experience or both as measured against established requirements such as standards or tests that enable the individual to perform a required function.

2.8 remanufacture: Activity involving disassembly, reassembly, and testing of the SSV/USV, with or without the replacement of parts, where machining, welding, heat treating or other manufacturing operations are employed.

Note: Remanufacture does not include the replacement of bodies.

2.9 repair: Any activity that involves either replacement with qualified parts or disassembly/reassembly of the SSV/USV. Repair may be offsite or onsite as described below.

2.9.1 offsite repair: Activity performed at a location other than the equipment installation site which restores the equipment to its original performance meeting the requirements of the edition of API Spec 6A in effect at the time of original manufacture, as a minimum.

2.9.2 onsite repair: Activity performed in accordance with this RP at the equipment installation site.

2.10 Surface Safety Valve (SSV): An automatic wellhead valve assembly that will close upon loss of power supply. When used in this standard it includes the SSV valve, SSV actuator, and heat sensitive lock-open device.

2.11 SSV/USV actuator: The device that causes the SSV/USV valve to open when power is supplied and to automatically close when power is lost or released.

2.12 SSV/USV valve: The portion of the SSV/USV that contains the wellstream and shuts off flow when closed.

2.13 tree, christmas: An assembly of valves and fittings used for production control that includes, as applicable, the tubing head top flange, the bottom most master valve, the crown valve (swabbing valve), the wellhead choke, and all valves and fittings in between.

2.14 valve, master: A valve located in the vertical run of a christmas tree whose primary purpose is to shut off well flow.

2.15 valve, wing: A valve located on the christmas tree, but not in the vertical run, which can be used to shut off well flow.

2.16 Underwater Safety Valve (USV): An automatic valve assembly (installed at an underwater wellhead location) that will close upon loss of power supply. When used in this standard, it includes the USV valve and USV actuator.

3 Receiving Inspection

3.1 Upon receipt of the SSV/USV at the wellsite, check the SSV/USV documentation to verify the following:

- a. The serial numbers on the SSV/USV correspond to those recorded on the accompanying receiving report.
- b. The SSV/USV valve and SSV/USV actuator are the proper size and pressure rating for the service intended.
- c. The SSV/USV valve is marked for the class of service (14D valves) or material class (6A, 10.20 valves) to which it may be subjected as outlined in API Spec 6A.

3.2 Check the SSV/USV for visible damage that might impair its proper operation.

Note: Disassembly of the SSV/USV for inspection must not be attempted by other than qualified personnel and should be in accordance with the manufacturer's, operating manual.

4 Installation and Maintenance

4.1 The SSV should be the second valve in the wellhead flowstream (e.g., if two master valves are used, the SSV should be the top master valve; if a single master valve is used, the SSV should be the wing valve). The USV should be in a practical location in the wellhead flowstream and within reasonable proximity of the well bore.

4.2 Installation and maintenance of SSVs/USVs should be performed by a qualified person(s).

4.3 Installation procedures outlined in the operating manual should be followed.

4.4 All supply lines should be cleared of foreign matter prior to hookup.

4.5 The SSV actuator supply medium (gas or liquid) should be clean and noncorrosive. If pneumatic, it should be free from solids, liquid hydrocarbons, and water or vapor. Hydraulic fluid should be free from gases and solids. Hydraulic fluid is normally used as the USV actuator supply medium.

4.6 End connection bolting and ring gaskets for SSVs should meet the requirements of API Spec 6A. Installation of bolting should be done in accordance with API Spec 6A. Where applicable, installation of USV bolting and ring gaskets should be in accordance with API Spec 6A.

4.7 After installation, but prior to application of any wellstream fluid or pressure, the SSV/USV valve should be operated several times to ensure smooth operation. Continuity should be checked between the shutdown controls and SSV/USV to assure proper operation of the complete system.

4.8 After installation on the well, the SSV should be tested in accordance with 6.1. The USV should be tested in accordance with 6.2.

4.9 Periodic inspection and maintenance of SSVs/USVs are necessary. Each SSV/USV should be tested at specified regular intervals as dictated by field experience, operator's policy and governmental regulations. The test should consist of an operating and pressure holding test as referenced in 6.1. For USVs, the test is described in 6.2.

4.10 Maintenance should be performed in accordance with the manufacturer's operating manual. The SSV should be properly lubricated as recommended in the manufacturer's operating manual, or more often if dictated by field experience. Lubricants and sealants used should be as prescribed in the manufacturer's operating manual or an acceptable alternate. The interior of an uncoated or unprotected actuator should be greased as often as necessary to prevent rusting.

4.11 The following should be considered when determining the USV installation depth:

- a. Installation depth should be determined according to the manufacturer's instructions.
- b. Pressure gradient of seawater/control line fluid.
- c. Calculated tubing pressure at USV during the open flow conditions.
- d. Operating friction as related to type of USV and sealing elements.
- e. Safety factor.

5 Repair**5.1 ONSITE REPAIR OF SSVS/USVS**

5.1.1 Onsite repair should be accomplished by a qualified person(s).

5.1.2 Onsite repair does not include the replacement of the SSV/USV valve body.

5.1.3 Replacement parts should be qualified parts and should be documented on the SSV/USV Repair Record Sheet (Exhibit 2). Qualified parts shall meet or exceed design requirements for the original parts.

5.1.4 Testing should be performed in accordance with 6.3.

5.1.5 Documentation: completed copies of the SSV/USV Repair Record Sheet (Exhibit 2) and the SSV/USV Functional Test Data Sheet for Onsite Repairs (Exhibit 3).

5.2 OFFSITE REPAIR/REMANUFACTURE OF SSVS/USVS

5.2.1 Offsite repair/remanufacture is not addressed in this RP. These operations should be performed at a facility where the procedures, specifications and quality control allow restoration of the equipment to its original performance meeting the requirements of the edition of API Specs 6A or 14D in effect at the time of original manufacture, as a minimum. Exhibit 2 and Exhibit 4 may be used for documentation.

6 Testing Procedures**6.1 PERIODIC SSV OPERATING AND PRESSURE HOLDING TEST****6.1.1 SSV Operating Test**

- a. Shut-in well.
- b. Close SSV.
- c. Open SSV.
- d. Return well to production.

6.1.2 SSV Pressure Holding Test

- a. Shut-in well and SSV as for operation test.
- b. Position wing and flowline valves to permit pressure to bleed off downstream of SSV.
- c. With pressure on upstream side of SSV, open bleed valve downstream of SSV and check for continuous flow. If sustained liquid flow exceeds 400 cubic centimeters per minute (0.4 cubic decimeters per minute) or gas flow exceeds 15 standard cubic feet per minute (611.6 cubic meters per day) during the pressure holding test, the SSV should be repaired or replaced. Test duration should be a minimum of 5 minutes.
- d. Close bleeder valve.
- e. Return well to production.

6.2 PERIODIC USV OPERATING AND PRESSURE HOLDING TEST**6.2.1 USV Operating Test**

- a. Shut-in well.
- b. Close USV.

- c. Open USV.
- d. Return well to production.

6.2.2 USV Pressure Holding Test

Each operator should use a method appropriate to his system to demonstrate the pressure integrity of the USV and quantify build-up rates. The following are two options offered for general guidance only:

- a. Option 1: Perform test as in 6.1.2.
- b. Option 2:
 - 1. Shut-in well and USV as for operation test (see 6.1.2a and 6.1.2b) and close downstream header or flowline valve.
 - 2. With pressure on upstream side of the USV, measure pressure buildup in the flowline versus time. If the absolute pressure buildup in the confined line segment downstream of the USV is in excess of that which represents a flow rate of 400 cubic centimeters per minute (0.4 cubic decimeter per minute) of liquid or 15 standard cubic feet per minute (611.6 cubic meters per day) of gas, the USV should be repaired or replaced. An example with calculations is given in Appendix A. Test duration should be a minimum of 5 minutes.
 - 3. Return well to production.

6.3 TESTING AFTER ONSITE REPAIRS

6.3.1 General

After onsite repair, a SSV/USV should be subjected to the appropriate test(s) listed in 6.3.2 to demonstrate proper assembly and operation. When repair on the SSV/USV actuator does not affect the SSV/USV valve, testing may be limited to that required in 6.1.1 or 6.2.1.

The test results should be documented on an SSV/USV Functional Test Data Sheet for Onsite Repairs similar to the example shown in Exhibit 3.

6.3.2 Testing

Recommendations for testing SSVs/USVs following onsite repairs are stated below. Testing may be limited according to onsite repairs performed.

6.3.2.1 *Onsite repairs where the SSV/USV actuator pressure containing seals are broken or disturbed.* The SSV/USV actuator should be tested for leakage using the SSV/USV actuator media. Test pressure should be normal field operating supply pressure. No leakage is allowed.

6.3.2.2 *Onsite repairs that might affect the alignment of the gate (plug) and seats.* The SSV/USV valve should be opened and checked visually or, if possible, with a drift mandrel for proper alignment.

6.3.2.3 *Onsite repairs that might affect operation of the SSV/USV.* The complete assembly should be tested for operational integrity; cycle the assembly fully open and fully closed three times with the SSV/USV valve body at ambient pressure or at wellhead shut-in tubing pressure (SITP) with no flow. (If equipment through the first downstream block valve will not withstand full wellhead SITP, conduct this test at the working pressure of the downstream equipment.)

6.3.2.4 *Onsite repairs that require breaking or disturbing a pressure containing seal in the SSV/USV valve.* The SSV/USV valve seals should be tested for leakage with the SSV/USV in a fully or partially open position and with the SSV/USV valve body exposed to maximum wellhead SITP. Test duration should be a minimum of 5 minutes with no leakage. (If equipment through the downstream block valve will not withstand full wellhead SITP, conduct this test at the working pressure of the downstream equipment.)

6.3.2.5 *Onsite repairs that might affect the SSV/USV valve seat seal.* The SSV/USV valve seat should be tested according to 6.1 or 6.2 following the test prescribed in 6.3.2.4 above.

7 Failure Reporting

User Recommendation: The operator of SSV/USV equipment repaired to this standard should provide a written report of equipment failure to the manufacturer. This report should include, as a minimum, the information in Exhibit 1 and a copy of the SSV/USV Repair Record Sheet (Exhibit 2).

8 Documentation Requirements

An operator complying with this standard should retain the following documentation on SSVs/USVs purchased in accordance with API Spec 6A:

- Operating manual.
- SSV/USV Repair Record Sheet (Exhibit 2), SSV/USV Functional Test Data Sheet (Exhibit 3 or 4, as applicable), repair records, and personnel.
- Failure Report for Surface Safety Valves (SSV) and Underwater Safety Valves (USV) (Exhibit 1).
- Equipment location, routine tests and maintenance records.

9 Miscellaneous

9.1 On an SSV, if a lock-open device is necessary, it should be a heat sensitive type.

9.2 Reference should be made to API RP 14C, Appendix C, C.2, for associated power supply and control systems for SSVs.

Exhibit 1—Failure Report for Surface Safety Valves (SSVs) and Underwater Safety Valves (USVs) (Minimum Data) (Example)

<p>Failure _____ of SSV/USV actuator _____</p> <p>SSV/USV valve _____</p> <p>Heat sensitive lock-open device _____ (not required for USVs)</p> <p>To be completed by operator:</p> <p>1. Identification:</p> <ol style="list-style-type: none"> 1.1 Operator. 1.2 Date. 1.3 Field and/or area. 1.4 Lease name and well number. 1.5 Type device: makes, models, sizes, serial numbers (include data on both SSV/USV valve and SSV/USV actuator). <p>2. Well data:</p> <ol style="list-style-type: none"> 2.2 Well test rate. Include percent sand, H₂S, CO₂ 2.3 Well pressures and temperatures: (surface). <p>3. Description of failure:</p> <ol style="list-style-type: none"> 3.1 Suspected cause. 3.2 Field conclusions. 	<p>To be completed by manufacturer:</p> <ol style="list-style-type: none"> 4. Failed components. Include provision to list failed components 5. Miscellaneous failure. Include provision to list associated equipment failure. 6. Cause of failure. Include provision to list probable and secondary causes. 7. Corrective action. Include provision to list all corrective action taken. 8. Submitted by: <ol style="list-style-type: none"> 8.1 Include provision to list any other information the operator deems important. 8.2 Mode of failure. 8.3 Leakage rate. 8.4 SSV/USV actuator control fluid 8.5 Copy sent to the originator. 9. Submitted by: <p>Signatures of qualified person (inspector) and operator's representative.</p> <p>_____</p> <p>_____</p>
--	---

EXHIBIT 2—SSV/USV REPAIR RECORD SHEET (EXAMPLE)

Location

Company (operator) _____

Lease no. _____ Field _____

Platform _____ Well No. _____

SSV/USV Valve Data

Manufacturer _____

SSV/USV valve catalog or model no. _____ Serial no. _____ Size _____

Rated working pressure _____ Temp. rating max. _____ Min. _____

SSV/USV valve bore _____ Class of service _____

SSV/USV Actuator Data

Manufacturer _____

SSV/USV actuator catalog or model no. _____ Serial no. _____ Size _____

Rated working pressure _____ Temp. rating max. _____ Min. _____

Part No. of Replaced Part(s)	Qty.	Description	Traceability/Reference No.
Prepared by:		Company:	Date:

EXHIBIT 3—SSV/USV FUNCTIONAL TEST DATA SHEET FOR ONSITE REPAIRS (EXAMPLE)

Location

Company (operator) _____
 Lease no. _____ Field _____
 Platform _____ Well no. _____

SSV/USV Valve Data

Manufacturer _____
 SSV/USV valve catalog or model no. _____ Serial no. _____ Size _____
 Rated working pressure _____ Temp. rating max. _____ Min. _____
 SSV/USV valve bore _____ Class of service _____

SSV/USV Actuator Data

Manufacturer _____
 SSV/USV actuator catalog or model no. _____ Serial no. _____ Size _____
 Rated working pressure _____ Temp. rating max. _____ Min. _____

Functional Test Date _____

I. SSV/USV Actuator Seal Test

Performed by: _____

Normal operating pressure _____

Actual test pressure _____ Test media _____

II. Drift Test

Performed by: _____

Drift mandrel inspection: Yes _____ No _____ OD _____

Visual inspection: Yes _____ No _____

III. SSV/USV Operation Test

Performed by: _____

Number of cycles completed with SSV/USV valve body at atmospheric pressure _____

Number of cycles completed with SSV/USV valve body exposed to SITP _____

IV. SSV/USV Valve Leakage Test

Performed by: _____

Well SIT _____ Test pressure _____

Test time _____

Leakage observed: Yes _____ No _____

V. SSV/USV Valve Seat Leakage Test

Performed by: _____

Well SITP _____ Test pressure _____

Test time _____

Leakage observed: Yes _____ No _____

Performed by: _____

Company: _____

Date: _____

EXHIBIT 4

SSV/USV FUNCTIONAL TEST DATA SHEET FOR OFFSITE REPAIRS (EXAMPLE)

Location

Company (operator) _____

Lease no. _____ Field _____

Platform _____ Well no. _____

SSV/USV Valve Data

Manufacturer _____

SSV/USV actuator catalog or model no. _____ Serial no. _____ Size _____

Rated working pressure _____ Temp. rating max. _____ Min. _____

SSV/USV valve bore _____ Class of Service _____

SSV/USV Actuator Data

Manufacturer _____

SSV/USV actuator catalog or model no. _____ Serial no. _____ Size _____

Rated working pressure _____ Temp. rating max. _____ Min. _____

Functional Test Date _____

I. SSV/USV Actuator Seal Test

Performed by: _____

Pneumatic _____ Hydraulic _____

At 20% of working pressure rating

Beginning time _____ Test gauge pressure reading _____

Ending time _____ Test gauge pressure reading _____

At 80% of working pressure rating

Beginning time _____ Test gauge pressure reading _____

Ending time _____ Test gauge pressure reading _____

II. Drift Test

Performed by: _____

Drift Mandrel _____

Visual Inspection _____

III. SSV/USV Operation Test

Performed by: _____

Number of cycles completed _____

IV. SSV/USV Valve Body and Bonnet Hydrostatic Test

Performed by: _____

Required test pressure _____

Primary pressure holding period

Beginning time _____ Test gauge pressure reading _____

Ending time _____ Test gauge pressure reading _____

Secondary pressure holding period

Beginning time _____ Test gauge pressure reading _____

Ending time _____ Test gauge pressure reading _____

V. SSV/USV Valve Seat Test

Performed by: _____

SSV/USV valve type: uni-directional _____ bi-directional _____

Required test pressure _____

Beginning time _____ Test gauge pressure reading _____

Ending time _____ Test gauge pressure reading _____

Secondary seal test (pressure applied from downstream end)

Beginning time _____ Test gauge pressure reading _____

Ending time _____ Test gauge pressure reading _____

Certified by: _____

Title: _____

Company: _____

Date: _____

APPENDIX A—SAMPLE PRESSURE BUILDUP CALCULATION

For installations inaccessible to leakage flow monitoring or for installations piped into large volume flowlines or vessels (10 barrels or more), leakage may be monitored as a function of pressure increase per unit of time. For example, in the case of a long flowline, the flow may be monitored by closing the USV, bleeding the pressure to ambient in the flowline segment and closing the first convenient isolation valve. Pressure increase in that isolated volume can then be monitored per unit of time; if the resulting increase is higher than specified in 6.2.2, Option 2, the valve should be repaired or replaced.

Note: The following examples are merely examples for illustration purposes only. [Each company should develop its own approach.] They are not to be considered exclusive or exhaustive in nature. API makes no warranties, express or implied for reliance on or any omissions from the information contained in this document.

A.1 Example

TFL flowline, 2.375 in. OD, 1.996 in. ID, 2583 ft long.

Capacity = 56.13 cu ft.

Temperature = 80°F or 540° Rankine.

Standard temperature = 60°F or 520° Rankine.

Initial pressure (P_1) = 0 psig = 14.7 psia or 2117 psfa.

Produced gas liquid ratio = 1500 SCF/bbl or 267.1 SCF/cu ft.

$Z = 1.0$, dimensionless compressibility factor (change negligible).

A.2 Solution

Theoretical liquid capacity of line:

267.1 cu ft of gas at 80°F occupies 257.2 cu ft under standard conditions.

$$267.1 \times \frac{520}{540} = 257.2 \text{ cu ft}$$

$$56.13 \text{ cu ft} \times \frac{1 \text{ cu ft liquid}}{257.2 \text{ cu ft gas}} = 0.22 \text{ cu ft liquid}$$

Gas capacity of line:

$$56.13 \text{ cu ft} - 0.22 \text{ cu ft} = 55.91 \text{ cu ft}$$

Limiting volume increase (due to leakage) is 15 SCF/min or 900 SCF/hr. This calculation assumes a 1 hour pressure buildup test.

a. Determine the initial moles of gas in the flowline:

$$P_1 V_1 = Z n_1 {}^\circ R T_1$$

where

$$P_1 = 2117 \text{ psfa}$$

$$V_1 = 55.91 \text{ cu ft}$$

$$Z = 1$$

$$n_1 = \text{initial number of moles}$$

$${}^\circ R = 1545 \frac{\text{ft-lb}}{{}^\circ R \text{ mole}}$$

$$T_1 = ^\circ\text{F} + 460 = 540 ^\circ\text{R}$$

$$n_1 = \frac{P_1 V_1}{Z ^\circ\text{R} T}$$

$$n_1 = \frac{(2117)(55.91)}{(1)(1545)(540)}$$

$$n_1 = 0.142 \text{ moles}$$

- b. Additional moles of gas entering the line (assuming negligible liquid enters the line):

$$P_2 V_2 = Z n_2 ^\circ\text{R} T_2$$

where

$$P_2 = 2117 \text{ psfa}$$

$$V_2 = 900 \text{ cu ft}$$

$$Z = 1$$

$$n_2 = \text{initial number of moles influx}$$

$$^\circ\text{R} = 1545 \frac{\text{ft-lb}}{^\circ\text{R mole}}$$

$$T_2 = 60^\circ\text{F} + 460 = 520^\circ\text{R}$$

$$n_2 = \frac{P_2 V_2}{Z ^\circ\text{R} T_2}$$

$$n_2 = \frac{(2117)(900)}{(1)(1545)(520)}$$

$$n_2 = 2.372 \text{ moles}$$

- c. Total moles of gas at end of 1 hour test:

$$n_t = n_1 + n_2$$

$$n_t = 0.142 + 2.372 = 2.514 \text{ moles}$$

- d. Final pressure at 540°R , assuming all gas is at 80°F :

$$P_f V_1 = Z n_t ^\circ\text{R} T_f$$

where:

$$P_f = \text{Final pressure}$$

$$V_1 = 55.91 \text{ cu ft}$$

$$Z = 1$$

$$n_t = 2.514 \text{ moles}$$

$$^\circ\text{R} = 1545 \frac{\text{ft-lb}}{^\circ\text{R mole}}$$

$$T_f = 540^\circ R$$

$$P_f = \frac{ZN_t^\circ RT_f}{V_1}$$

$$P_f = \frac{(1)(2.514)(1545)(540)}{(55.91)}$$

$$P_1 = 37,514 \text{ psfa or } 260.5 \text{ psia}$$

$$P_1 = 260.5 - 14.7 = 245.8 \text{ psig}$$

The 246 lbs per square in. gauge increase represents the maximum allowable gas influx into the 2583 ft – 2³/₈ in. OD flowline during the 1 hour test.

Copyright American Petroleum Institute
Provided by IHS under license with API
No reproduction or networking permitted without license from IHS

APPENDIX B—SI UNITS

The conversion of English units shall be made in accordance with ISO 31-3.

Table B-1—SI Units

Quantity	U.S. Customary Unit	SI Unit
Area	1 square inch (in. ²)	645.16 square millimeters (mm ²) (exactly)
Flow Rate	1 barrel per day (bbl/d)	0.158987 cubic meters per day (m ³ /d)
	1 cubic foot per minute (ft ³ /min)	0.02831685 cubic meters per minute (m ³ /min) or 40.776192 cubic meters per day (m ³ /d)
Force	1 pound-force (lbf)	4.448222 newtons (N)
Impact Energy	1 foot pound-force (ft-lb)	1.355818 Joules (J)
Length	1 inch (in.)	25.4 millimeters (mm) (exactly)
	1 foot (ft)	304.8 millimeters (mm) (exactly)
Mass	1 pound (lb)	0.45359237 kilograms (kg) (exactly)
Pressure	1 pound-force per square inch (lbf/in. ²) or 1 pound per square inch (psi) (Note: 1 bar = 10 ⁵ Pa)	6894.757 pascals (Pa)
Strength or Stress	1 pound-force per square inch (lbf/in. ²)	6894.757 pascals (Pa)
Temperature	The following formula was used to convert degrees Fahrenheit (°F) to degrees Celsius (°C)	°C = $\frac{5}{9}$ (°F – 32)
Torque	1 inch pound-force (in-lbf)	0.112985 newton meters (N-m)
	1 foot pound-force (ft-lbf)	1.355818 newton meters (N-m)
Velocity	1 foot per second (ft/s)	0.3048 meters per second (m/s) (exactly)
Volume	1 cubic inch (in. ³)	16.387064 × 10 ⁻³ cubic decimeters (dm ³) (exactly)
	1 cubic foot (ft ³)	0.0283168 cubic meters (m ³) or 28.3168 cubic decimeters (dm ³)
	1 gallon (U.S.)	0.0037854 cubic meters (m ³) or 3.7854 cubic decimeters (dm ³)
	1 barrel (U.S.)	0.158987 cubic meters (m ³) or 158.987 cubic decimeters (dm ³)



2007 Publications Order Form

Effective January 1, 2007.

API Members receive a 30% discount where applicable.

The member discount does not apply to purchases made for the purpose of resale or for incorporation into commercial products, training courses, workshops, or other commercial enterprises.

Available through IHS:

Phone Orders: 1-800-854-7179 (Toll-free in the U.S. and Canada)
303-397-7956 (Local and International)

Fax Orders: 303-397-2740

Online Orders: global.ihs.com

Date: _____

☐ **API Member** (Check if Yes)

Invoice To (☐ Check here if same as "Ship To")

Name: _____

Title: _____

Company: _____

Department: _____

Address: _____

City: _____ **State/Province:** _____

Zip/Postal Code: _____ **Country:** _____

Telephone: _____

Fax: _____

E-Mail: _____

Ship To (UPS will not deliver to a P.O. Box)

Name: _____

Title: _____

Company: _____

Department: _____

Address: _____

City: _____ **State/Province:** _____

Zip/Postal Code: _____ **Country:** _____

Telephone: _____

Fax: _____

E-Mail: _____

Quantity	Product Number	Title	SO★	Unit Price	Total
	GX06A19	Spec 6A, Specification for Wellhead and Christmas Tree Equipment		\$232.00	

☐ **Payment Enclosed** ☐ **P.O. No.** (Enclose Copy) _____

☐ **Charge My IHS Account No.** _____

☐ **VISA** ☐ **MasterCard** ☐ **American Express** ☐ **Diners Club** ☐ **Discover**

Credit Card No.: _____

Print Name (As It Appears on Card): _____

Expiration Date: _____

Signature: _____

Subtotal

Applicable Sales Tax (see below)

Rush Shipping Fee (see below)

Shipping and Handling (see below)

Total (in U.S. Dollars)

★ **To be placed on Standing Order for future editions of this publication, place a check mark in the SO column and sign here:**

Pricing and availability subject to change without notice.

Mail Orders – Payment by check or money order in U.S. dollars is required except for established accounts. State and local taxes, \$10 processing fee, and 5% shipping must be added. Send mail orders to: **API Publications, IHS, 15 Inverness Way East, c/o Retail Sales, Englewood, CO 80112-5776, USA.**

Purchase Orders – Purchase orders are accepted from established accounts. Invoice will include actual freight cost, a \$10 processing fee, plus state and local taxes.

Telephone Orders – If ordering by telephone, a \$10 processing fee and actual freight costs will be added to the order.

Sales Tax – All U.S. purchases must include applicable state and local sales tax. Customers claiming tax-exempt status must provide IHS with a copy of their exemption certificate.

Shipping (U.S. Orders) – Orders shipped within the U.S. are sent via traceable means. Most orders are shipped the same day. Subscription updates are sent by First-Class Mail. Other options, including next-day service, air service, and fax transmission are available at additional cost. Call 1-800-854-7179 for more information.

Shipping (International Orders) – Standard international shipping is by air express courier service. Subscription updates are sent by World Mail. Normal delivery is 3-4 days from shipping date.

Rush Shipping Fee – Next Day Delivery orders charge is \$20 in addition to the carrier charges. Next Day Delivery orders must be placed by 2:00 p.m. MST to ensure overnight delivery.

Returns – All returns must be pre-approved by calling the IHS Customer Service Department at 1-800-624-3974 for information and assistance. There may be a 15% restocking fee. Special order items, electronic documents, and age-dated materials are non-returnable.

There's more where this came from.

The American Petroleum Institute provides additional resources and programs to the oil and natural gas industry which are based on API® Standards. For more information, contact:

- | | |
|---|--|
| • API Monogram® Licensing Program | Phone: 202-962-4791
Fax: 202-682-8070 |
| • American Petroleum Institute Quality Registrar (APIQR®) | Phone: 202-962-4791
Fax: 202-682-8070 |
| • API Spec Q1® Registration | Phone: 202-962-4791
Fax: 202-682-8070 |
| • API Perforator Design Registration | Phone: 202-962-4791
Fax: 202-682-8070 |
| • API ISO/TS 29001 Registration | Phone: 202-962-4791
Fax: 202-682-8070 |
| • API Training Provider Certification Program | Phone: 202-682-8490
Fax: 202-682-8070 |
| • Individual Certification Programs | Phone: 202-682-8064
Fax: 202-682-8348 |
| • Engine Oil Licensing and Certification System (EOLCS) | Phone: 202-682-8516
Fax: 202-962-4739 |
| • API PetroTEAM™ (Training, Education and Meetings) | Phone: 202-682-8195
Fax: 202-682-8222 |

Check out the API Publications, Programs, and Services Catalog online at www.api.org.



American Petroleum Institute

Helping You Get
The Job Done Right.®



1220 L Street, NW
Washington, DC 20005-4070
USA

202.682.8000

Additional copies are available through IHS
Phone Orders: 1-800-854-7179 (Toll-free in the U.S. and Canada)
303-397-7956 (Local and International)
Fax Orders: 303-397-2740
Online Orders: global.ihs.com

Information about API Publications, Programs and Services
is available on the web at www.api.org

Product No. G14H05